

Choosing the right anti-fatigue mat

Polyurethane/Nitril Rubber

Highly recommended ■
 Recommended ■
 Variable (contact Ergomat) ■
 Not recommended

	CLASSIC	COMPLETE BUBBLE	COMPLETE SMOOTH	EFB COMPLETE BUBBLE	EFS COMPLETE SMOOTH	DELUXE	INFINITY BUBBLE ESD	INFINITY SMOOTH ESD	INFINITY BUBBLE	INFINITY SMOOTH	INFINITY ULTRA-SMOOTH	BUBBLE DOWN	BASIC BUBBLE	BASIC SMOOTH	BASIC PLANO	Softline	Nitro	Nitril	Nitril ESD-Conductive	Industry	Nitril Smooth/ Plano	Nitril Smooth ESD-CON.	Hygiene
Dry usage area	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Wet usage area	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Static control	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Fire retardant	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Slip prevention	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Welding area/Embers	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Customized mats/Drawings	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Outdoor	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Mineral oils	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Vegetable oils	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Cooling/cutting fluids	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Cutting oils/fluids include esters and amines	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Alkaline liquids pH: 7-9,5	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Alkaline liquids pH: 9,5-14	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Acids pH: 2-7	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Acids pH: 0-2	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Disinfectants	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Chloride solutions in water	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Solvents (aromatic/aliphatic)	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Phthalates (and related softeners)/Ketones/Aldehyde/Esters/Amines	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Alcohol	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

User Instructions Polyurethane/Rubber

	Classic/Complete Bubble/Complete Smooth/Basic Bubble/Basic Smooth/EFB/EFS/ Bubble Down/Basic Plano	Deluxe/Infinity Bubble/Infinity Smooth	Softline/Nitro/Nitril/Nitril ESD/Nitril CON/Nitril F/Industry/Plano/Plano ESD/Plano CON	Hygiene/Safe Mat/Super Safe-Mat
Suitable for usage	Dry areas	Dry areas	Dry and wet areas	Dry and wet areas
Temperature	40° to 95° F 5° to 35° C	40° to 95° F 5° to 35° C	-40° to 195° F -40° to 90° C	-40° to 250° F -40° to 120° C
Cleaning	<ul style="list-style-type: none"> Sweeping Vacuuming Washing in mild soap (pH: 6-8) with subsequently careful wiping so all water is removed 	<ul style="list-style-type: none"> Sweeping Vacuuming Washing in mild soap (pH: 2-9,5). If the backside of the mat gets wet during the washing, the mat must lie upside down until it is dry and all the moisture has evaporated. 	<ul style="list-style-type: none"> Sweeping Vacuuming Wet mopping with mild soap (pH 5-9) Pressure washing 1,000 -1,500 PSI (70 - 100 BAR) at a minimum distance of 8" Autoclavable in 2'x3' (60 x 90 cm) size only. Dry the mat horizontally and flat. Avoid bending. 	<ul style="list-style-type: none"> Sweeping Vacuuming Wet mopping water based cleaning agent (pH 1-13) Pressure washing 1,000 - 1,500 PSI (70 - 100 BAR) at a minimum distance of 8" Autoclavable in 2'x3' (60 x 90 cm) size only Dry the mat horizontally and flat. Avoid bending.

Cleaning the mats is the responsibility of the end-user. Warranty will be voided on mats that are not appropriately maintained.



www.ergomat.com - info@ergomat.com
 US: +1-440-282-4651
 English (EU): +44 03308 280 084
 Scandinavia: +45 70 22 18 40
 German: +49 9524 30367-50
 French: +33 1 446 410 28
 Dutch: +31 73 613 05 30

